

READ ONLY

PACKAGED SYSTEMS

Gas/Electrics

YSC

- 3 – 10 ton
- R-410A
- Electro-mechanical or microprocessor controls
- Convertible airflow
- Phase monitor
- Discharge thermostat
- Crankcase heater (optional on 3 – 5 ton)
- Innovative features & options



YHC

- 3 – 10 ton
- R-410A
- Up to 17.50 SEER (3 – 5 ton)
- Up to 13.00 EER/15.00 IEER (7.5 – 10 ton)
- Electro-mechanical or microprocessor controls
- Convertible airflow
- Phase monitor
- Discharge thermostat
- Crankcase heater
- Innovative features & options

YSD/YSH/YHD/YHH

- 12.5 – 25 ton
- R-410A
- Up to 12.00 EER
- Up to 3 stages of cooling (high efficiency only)
- Microprocessor controls
- Dedicated downflow or horizontal
- Phase monitor
- Discharge thermostat
- Crankcase heater



GAC/GAD

- 15 – 25 ton
- R-410A
- Up to 11.00 EER
- Convertible Airflow on GAC models
- Phase monitor
- Configurable Footprint



LIMITED WARRANTY (years)

YSC and YHC	
Compressor	5
Heat Exchanger	5
Functional Parts	1
YSD/YSH/YHD/YHH (12.5 – 17.5 ton)	
Compressor	5
Heat Exchanger	5
Functional Parts	1
YSD/YSH/YHD/YHH (20 and 25 ton)	
Compressor	5
Heat Exchanger	1
Functional Parts	1
GAC/GAD (15 and 25 ton)	
Compressor	5
Heat Exchanger	5
Functional Parts	1

Air Conditioners

TSC

- 3 – 10 ton
- R-410A
- Electro-mechanical or microprocessor controls
- Convertible airflow
- Phase monitor
- Discharge thermostat
- Crankcase heater (optional on 3 – 5 ton)
- Innovative features & options



THC

- 3 – 10 ton
- R-410A
- Up to 17.50 SEER (3 – 5 ton)
- Up to 13.00 EER/15.00 IEER (7.5 – 10 ton)
- Electro-mechanical or microprocessor controls
- Convertible airflow
- Phase monitor
- Discharge thermostat
- Crankcase heater
- Innovative features & options

TSB/TSH/THD/THH

- 12.5 – 25 ton
- R-410A
- Up to 12.00 EER
- Up to 3 stages of cooling (high efficiency only)
- Microprocessor controls
- Dedicated downflow or horizontal
- Phase monitor
- Discharge thermostat
- Crankcase heater



EAC

- 15 – 25 ton
- R-410A
- Up to 11.00 EER
- Convertible Airflow on all models
- Phase monitor
- Configurable Footprint



LIMITED WARRANTY (years)

TSC and THC	
Compressor	5
Functional Parts	1
TSB/TSH/THD/THH (12.5 – 17.5 ton)	
Compressor	5
Functional Parts	1
TSB/TSH/THD/THH (20 and 25 ton)	
Compressor	5
Functional Parts	1
EAC (15 and 25 ton)	
Compressor	5
Functional Parts	1

Heat Pumps

WSC

- 3 – 10 ton
- R-410A
- Microprocessor controls
- Convertible airflow
- Phase monitor
- Discharge thermostat
- Crankcase heater
- Innovative features & options



WSD/WSH

- 12.5 – 20 ton
- R-410A
- Microprocessor controls
- Dedicated downflow or horizontal
- Built-in anti-short cycle, time delay relay and minimum on time controls
- Phase monitor
- Discharge thermostat
- Crankcase heater



LIMITED WARRANTY (years)

WSC	
Compressor	5
Functional Parts	1
WSD and WSH (12.5 – 15 ton)	
Compressor	5
Functional Parts	1
WSD and WSH (20 ton)	
Compressor	1
Functional Parts	1

SPLIT SYSTEMS

Air Conditioners/Heat Pumps

TTA – Cooling

- 6 – 25 ton
- Single, dual or manifolded compressors
- Microprocessor controls option
- Phase monitor
- Discharge thermostat
- Crankcase heater
- R-22 (on certain sizes) or R-410A

TWA – Heat Pump

- 6 – 20 ton
- Single or dual compressors
- Microprocessor controls standard
- Phase monitor
- Discharge thermostat
- Crankcase heater
- R-22 (on certain sizes) or R-410A



LIMITED WARRANTY (years)

TTA – Cooling	
Compressor	5
Functional Parts	1
TTA – Cooling (TTA240 and TTA300 only)	
Compressor	1
Functional Parts	1
TWA – Heat Pump	
Compressor	5
Functional Parts	1
TWA – Heat Pump (TWA240 only)	
Compressor	1
Functional Parts	1

Air Handlers

TWE-D

- 5 – 10 ton
- Single circuit air handler
- Upflow convertible to horizontal
- R-410A

TWE-E

- 5 – 25 ton
- Dual circuit air handler
- Upflow convertible to horizontal
- R-410A



LIMITED WARRANTY (years)

TWE-D and TWE-E	
Functional Parts	1

FACTORY-INSTALLED OPTIONS FOR LIGHT COMMERCIAL PACKAGED SYSTEMS



Dehumidification (Hot Gas Reheat) Option

Reduces humidity levels while increasing comfort levels within the comfort zone. Available on select tonnages.



Economizers

Factory-installed economizers come with three options for controls – dry bulb, reference enthalpy and comparative enthalpy. California Title 24-compliant, low leak economizers with fault detection and diagnostics are also available.



Tool-Less Hail Guard

Protects the condenser coil from vandalism or hail damage.



Supply And/Or Return Air Smoke Detector

With this option installed, if smoke is detected, all unit operations will shut down.



Hinged Access Doors

Easy access is provided to the filter, fan, heat, compressor and control sections for quicker service calls.



Through-The-Base Gas Connections

Installed gas piping with shut-off from outside for packaged gas/electrics.



Powered Or Unpowered Convenience Outlet

A GFCI, 120V, 15 amp, 2 plug convenience outlet, either powered or unpowered (downflow only).



Stainless Steel Progressive Tubular Heat Exchanger

The heat exchanger is corrosion resistant, using stainless steel throughout for 3 – 10 ton gas/electric models.

American Standard[®]
HEATING & AIR CONDITIONING

americanstandardair.com

American Standard Heating & Air Conditioning
6200 Troup Highway • Tyler, Texas 75707

Since American Standard Heating & Air Conditioning has a policy of continuous product improvement, it reserves the right to change specifications and design without notice. Read important energy cost and efficiency information available from your dealer.

© 2015 American Standard Heating & Air Conditioning All rights reserved

Pub. No. 10-3083-04 5/15